SAFETY DATA SHEET

Date Prepared: 2/26/2018

SDS No: 4350-SDS

Prime

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Prime

GENERAL USE: Heavy Duty Foaming Degreaser

PRODUCT CODE: 4350

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

Infotrac 800-535-5053

Perform Mfg 1624 S. 45th St. Kansas City KS 6

Kansas City, KS 66106

Customer Service: 913-722-1557 **E-Mail:** sales@performmfg.com

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion / Irritation, Category 1B Serious Eye Damage / Eye Irritation, Category 1

GHS LABEL

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)



Corrosion

SIGNAL WORD: DANGER HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

H290: May be corrosive to metals.

PRECAUTIONARY STATEMENTS

Prevention:

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash face, hands and any expose skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minuts. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P102: Keep out of reach of children.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Glycine, N,n'-1,2-ethanediylbis[n-(carboxymethyl)-, Tetrasodium Salt	< 5	64-02-8
sodium metasillcate	< 5	6834-92-0
Sodium Dodecylbenezene Sulfonate	< 5	25155-30-0
Sodium Hydroxide	< 10	1310-73-2
Sodium C14-c16 Olefin Sulfonate	< 5	68439-57-6

4. FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center Immediately if irritation persist.

SKIN: Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. Call a POISON CENTER or doctor / physician. Remove and wash contaminated clothing before re-use.

INGESTION: Rinse mouth. Do NOT induce vomiting. Call a physician or Poison Control Center.

INHALATION: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician or Poison Control Center if you feel unwell.

NOTES TO PHYSICIAN: Treat symptomatically. Product is a corrosive material. Use of gastric lavage or emesis is contraindicate. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and hugh pulse pressure.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action should be taken involving any personal risk or without suitable training.

EXTINGUISHING MEDIA: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

OTHER CONSIDERATIONS: In a fire or if heated, a pressure increase will occur and the container may burst.

FIRE FIGHTING PROCEDURES: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: None Expected.

SENSITIVITY TO IMPACT: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products may include the following materials: carbon dioxide, carbon monoxide, and other toxic gases or vapors.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if not water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated adsorbent material may pose the same hazard as the spilled product.

GENERAL PROCEDURES: No action should be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate, put on appropriate personal protective equipment.

RELEASE NOTES: Take Steps to avoid release into the environment, if safe to do so.

SPECIAL PROTECTIVE EQUIPMENT: Avoid breathing vapors and provide adequate ventilation. As conditions warrant, wear a NIOSH approved self-contained breathing apparatus, or respirator, and appropriate personal protection (rubber boots, safety goggles, and heavy rubber gloves).

7. HANDLING AND STORAGE

HANDLING: Ensure adequate ventilation. Wear personal protective equipment as required based on a risk assessment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

STORAGE: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food or drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
	EXPOSURE LIMITS				
		OSHA PEL Supplier OEL		er OEL	
Chemical Name		ppm	mg/m³	ppm	mg/m³
Sodium Dodecylbenezene Sulfonate	TWA			NL	NL
	STEL			NL	NL
Sodium Hydroxide ——	TWA		2	NL	NL
	STEL			NL	NL
Sodium C14-c16 Olefin Sulfonate	TWA			NL	NL
	STEL			NL	NL

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: If splashes are likely to occur, wear: Tightly fitting safety goggles and face shield.

SKIN: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

RESPIRATORY: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Fragranced

ODOR THRESHOLD: No data available

APPEARANCE: Colored liquid

pH: 13 to 14

FLASH POINT AND METHOD: > (212°F)

AUTOIGNITION TEMPERATURE: Not Available

VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: > (212°F) FREEZING POINT: < (32°F) MELTING POINT: Not Available POUR POINT: Not Available

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Complete **EVAPORATION RATE:** Not Available

DENSITY: Not Available

SPECIFIC GRAVITY: Not Available

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions. **POLYMERIZATION:** Hazardous polymerization does not occur.

CONDITIONS TO AVOID: None known.

POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of storage and use, hazardous reactions will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition can lead to release of irritating gases and vapors.

INCOMPATIBLE MATERIALS: Strong oxidizing agents. Strong acids, Organic materials

11. TOXICOLOGICAL INFORMATION

ACUTE

DERMAL LD₅₀: > 2000 mg/kg **ORAL LD**₅₀: > 2000 mg/kg

EYE EFFECTS: Causes serious eye irritation. **SKIN EFFECTS:** Causes severe skin burns.

CHRONIC: No data available
SUBCHRONIC: No data available
SENSITIZATION: No data available
NEUROTOXICITY: No data available
GENETIC EFFECTS: No data available

REPRODUCTIVE EFFECTS: No data available

TARGET ORGANS: Respiratory System, Eyes and Skin

MUTAGENICITY: No data available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available

ECOTOXICOLOGICAL INFORMATION: No data available **BIOACCUMULATION**/**ACCUMULATION:** No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

EMPTY CONTAINER: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Liquid, N.O.S. **TECHNICAL NAME:** (Contains: Sodium Hydroxide)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN1760
PACKING GROUP: II
LABEL: Corrosive

OTHER SHIPPING INFORMATION: All products offered for domestic ground transportation that meet the following exceptions for Class 8 (Corrosive Materials) will be packaged and shipped as "Limited Qty".

- (1) For Corrosive Materials in Packing Group II, inner packaging not over 1.0 L (0.3 Gallon) net capacity each for liquids or not over 1.0 kg (2.2 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.
- (2) For Corrosive Materials in Packing Group III, inner packaging not over 5.0 L (1.3 Gallons) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: No

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Sodium Dodecylbenezene Sulfonate	< 5	1,000
Sodium Hydroxide	< 10	1,000


TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Glycine, N,n'-1,2-ethanediylbis[n-(carboxymethyl)-, Tetrasodium Salt	64-02-8
sodium metasillcate	6834-92-0
Sodium Dodecylbenezene Sulfonate	25155-30-0
Sodium Hydroxide	1310-73-2
Sodium C14-c16 Olefin Sulfonate	68439-57-6

16. OTHER INFORMATION

PREPARED BY: KH Date Prepared: 2/26/2018

HMIS RATING HEALTH 2 FLAMMABILITY 0 PHYSICAL HAZARD 0 PERSONAL PROTECTION C



MANUFACTURER DISCLAIMER: The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. the information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. the information relates only to specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.