ENZ-O-MATIC GP

General Purpose Digestant

NZ-O-MATIC GP is a general purpose powder digestant. This product contains a powerful blend of anaerobic and aerobic cultures designed to digest and liquefy organic waste quickly and without odors. The natural enzymes break down proteins, starches, animal and vegetable fats, oils and cellulose (paper) to create the best environment for waste digestion.

USE ON

- Sinks
- Garbage Disposals
- Grease Traps
- Septic Tanks
- Restrooms
- Porta Toilets
- Drain Lines

USE IN

- Schools
- Hospitals
- Nursing Homes
- Apartments
- · Athletic Clubs
- Restaurants
- · Hotels/Motels

USE FOR

- Organic Waste
- Grease
- Fats
- Protein
- Cellulose

DIRECTIONS FOR USE

The dry bacteria cultures and enzymes in this formula must be activated by premixing in warm water (85-100 F). DO NOT USE HOT WATER! Pour slurry into drains, toilets, traps, etc., to be treated.

DRAINS: To open clogged or slow drains, dissolve 5 tablespoons in 2 cups warm water. Pour into drain and allow to work overnight. For regular drain maintenance, use 2 tablespoons per week. For drains that receive large amounts of organic matter (kitchen, floor, laundry sinks and drains), use 4 to 6 tablespoons two or three times per week. This digestant product helps to maintain free-flowing and fresh smelling conditions in all toilets, urinals, drains, garbage disposals, grease traps and plumbing. Best results are obtained by adding the digestant at the end of the day or other period of lowest flow. To prevent loosened debris from causing obstructions, always begin the treatment program by treating the lower floors first. Disinfectant products and harsh drain openers may kill the bacteria. Allow several hours after the use of these products, then re-treat with digestant.

GREASE TRAPS: For initial treatment, use 1 pound for each 20 cubic feet of trap capacity. Repeat this initial treatment for three weeks, use 1/2 pound per 20 cubic feet weekly.

SEPTIC SYSTEMS: Use 1/2 pound for each 500 gallons of system capacity (or 1 pound per 5 people using the system) as an initial treatment. Flush into toilet. Then use 1/4 pound per month for maintenance. To keep drain field and leach beds operating properly, dissolve 1 pound in warm water and pour into distribution box. Repeat this treatment weekly until flow is improved.

PIT TOILETS: To reduce odors, increase capacity, and liquefies solids in pit toilets, use 1/4 to 1/2 pound per 500 gallons of capacity. Make digestant additions weekly. Do not use formaldehyde preservatives or disinfectants in treated toilets.



Kansas City, KS. - 800-423-9861

Products That Perform!