Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 *Reviewed on 04/24/2026*

1 Identification

· **Product identifier**

· **Trade name: Easy**
· **Other means of identification**

· **Product number:** 4100
· **Relevant identified uses of the substance or mixture and uses advised against**
· **Product Description:** Foaming Decarbonate

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Perform Mfg
1624 S. 45th St.
Kansas City, KS 66106
Customer Service: 913-722-1557
E-Mail: sales@performmfg.com
· **Emergency telephone number:** Infotrac: US & Canada: 1-800-535-5053 | International 1-352-323-3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

GHS08 Health hazard

Carcinogenicity 2	H351 Suspected of causing cancer.
Specific target organ toxicity (repeated exposure) 2	H373 May cause damage to organs through prolonged or repeated exposure.

GHS05 Corrosion

Skin corrosion 1A	H314 Causes severe skin burns and eye damage.
Eye damage 1	H318 Causes serious eye damage.

GHS07

Sensitization - skin 1	H317 May cause an allergic skin reaction.

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**

GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Disodium Cocoampho Dipropionate
Potassium hydroxide
Cocamide DEA
dipropylene glycol butyl ether
Limonene
· **Hazard statements**
Causes severe skin burns and eye damage.

(Contd. on page 2)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 *Reviewed on 04/24/2026*

Trade name: Easy

(Contd. of page 1)

May cause an allergic skin reaction.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

· ***Precautionary statements***
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· ***Unknown acute toxicity:***
This value refers to knowledge of known, established toxicological or ecotoxicological values.
0 % of the mixture consists of component(s) of unknown toxicity.

· ***Information pertaining to particular dangers for man and environment:***

· ***Classification system:*** *NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme*

· ***NFPA ratings (scale 0 - 4)***

Health = 3
Fire = 1
Reactivity = 0

· ***HMIS-ratings (scale 0 - 4)***

*Health = *3*
Fire = 1
Reactivity = 0

· ***Other hazards***

· ***Results of PBT and vPvB assessment***

· ***PBT:*** *Not applicable*

· ***vPvB:*** *Not applicable*

· ***Classification according to (d)(1)(ii) of § 1910.1200***
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· ***Hazards not otherwise classified (HNOC)***
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· ***Chemical characterization: Mixtures***

· ***Description:*** *Mixture of the substances listed below with nonhazardous additions.*

(Contd. on page 3)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 2)

· **Dangerous components:**		
CAS: 68604-71-7	Disodium Cocoampho Dipropionate Eye damage 1, H318; Sensitization - skin 1, H317	≥5–≤7%
CAS: 1310-58-3 RTECS: TT 2102000	Potassium hydroxide Skin corrosion 1A, H314; Acute toxicity - oral 4, H302 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	≥5–≤7%
CAS: 68603-42-9	Cocamide DEA Carcinogenicity 2, H351; Specific target organ toxicity (repeated exposure) 2, H373; Eye damage 1, H318; Skin irritation 2, H315; Sensitization - skin 1, H317	≥3–<5%
CAS: 111-76-2 RTECS: KJ 8575000	Glycol Ether EB (2-butoxyethanol) Acute toxicity - oral 4, H302; Acute toxicity - dermal 4, H312; Acute toxicity - inhalation 4, H332; Skin irritation 2, H315; Eye irritation 2A, H319; Specific target organ toxicity (single exposure) 3, H335-H336; Flammable liquids 4, H227	1–5%
CAS: 29911-28-2	dipropylene glycol butyl ether Specific target organ toxicity (repeated exposure) 2, H373; Eye irritation 2A, H319; Flammable liquids 4, H227	0.5–1.5%
CAS: 67-56-1 RTECS: PC 1400000	Methanol Flammable liquids 2, H225; Acute toxicity - oral 3, H301; Acute toxicity - dermal 3, H311; Acute toxicity - inhalation 3, H331; Specific target organ toxicity (single exposure) 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	0.1–1%
CAS: 111-42-2 RTECS: KL 2975000	Diethanolamine Carcinogenicity 2, H351; Specific target organ toxicity (repeated exposure) 2, H373; Eye damage 1, H318; Acute toxicity - oral 4, H302; Skin irritation 2, H315	≥0.1–<1%
CAS: 138-86-3 RTECS: OS 8100000	Limonene Flammable liquids 3, H226; Skin irritation 2, H315; Sensitization - skin 1, H317	≥0.1–<1%

· **Additional information:**
The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
If irritation occurs, consult a doctor.
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:**
Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation occurs, consult a doctor.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 4)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 3)

If easy to do so, remove contact lenses if worn.
Have eyes examined and tested by medical personnel.
If thermal burn occurs, flush area with cold water and get immediate medical attention.

· **After swallowing:**
Do not induce vomiting without medical advice.
Rinse mouth out with water.
Never give anything by mouth to an unconscious person.
If swallowed and symptoms occur, consult a doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers / surface or ground water.

· **Methods and material for containment and cleaning up:**
SMALL SPILL: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if not water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated adsorbent material may pose the same hazard as the spilled product.
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

· **Protective Action Criteria for Chemicals**
Protective Action Criteria (PACs) are essential components for planning and response to uncontrolled releases of hazardous chemicals.

· **PAC-1:**
PAC 1: Mild, transient health effects.

1310-58-3	Potassium hydroxide	0.18 mg/m3
111-76-2	Glycol Ether EB (2-butoxyethanol)	20 ppm
67-56-1	Methanol	530 ppm
56-81-5	Glycerol	45 mg/m3
111-42-2	Diethanolamine	3.0 mg/m3

(Contd. on page 5)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 4)

64-02-8	Tetrasodium ethylenediaminetetraacetate	5.3 mg/m3
2836-32-0	Sodium Glycolate	21 ppm
5989-27-5	D-Limonene	15 ppm
1310-73-2	Sodium hydroxide	0.50 mg/m3
112-31-2	DECANAL	11 mg/m3
8006-64-2	Turpentine, oil	60 ppm

· **PAC-2:**
PAC 2: Irreversible or other serious health effects that could impair the ability to take protective action.

1310-58-3	Potassium hydroxide	2.0 mg/m3
111-76-2	Glycol Ether EB (2-butoxyethanol)	67 ppm
67-56-1	Methanol	2100 ppm
56-81-5	Glycerol	180 mg/m3
111-42-2	Diethanolamine	22 mg/m3
64-02-8	Tetrasodium ethylenediaminetetraacetate	59 mg/m3
2836-32-0	Sodium Glycolate	230 ppm
5989-27-5	D-Limonene	67 ppm
1310-73-2	Sodium hydroxide	5.0 mg/m3
112-31-2	DECANAL	120 mg/m3
8006-64-2	Turpentine, oil	120 ppm

· **PAC-3:**
PAC 3: Life-threatening health effects.

1310-58-3	Potassium hydroxide	54 mg/m3
111-76-2	Glycol Ether EB (2-butoxyethanol)	700 ppm
67-56-1	Methanol	7200 ppm
56-81-5	Glycerol	1100 mg/m3
111-42-2	Diethanolamine	130 mg/m3
64-02-8	Tetrasodium ethylenediaminetetraacetate	350 mg/m3
2836-32-0	Sodium Glycolate	1400 ppm
5989-27-5	D-Limonene	170 ppm
1310-73-2	Sodium hydroxide	50 mg/m3
112-31-2	DECANAL	740 mg/m3
8006-64-2	Turpentine, oil	1500 ppm

· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Avoid contact with skin, eyes and clothing.
Keep out of reach of children.
Wear protective equipment.
· **Information about protection against explosions and fires:** Keep respiratory protective device available.

(Contd. on page 6)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 5)

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

1310-58-3 Potassium hydroxide	
REL	Ceiling limit value: 2 mg/m³
TLV	Ceiling limit value: 2 mg/m³
111-76-2 Glycol Ether EB (2-butoxyethanol)	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI, A3
67-56-1 Methanol	
PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI-C
111-42-2 Diethanolamine	
REL	Long-term value: 15 mg/m³, 3 ppm
TLV	Long-term value: 1* mg/m³, 0.2 ppm Skin; *inhalable fraction and vapor, A3
138-86-3 Limonene	
TLV	Long-term value: 3 ppm DSEN
WEEL	Long-term value: 30 ppm

· **Regulatory information**
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)
PEL: Guide to Occupational Exposure Values (OSHA PELs)
WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

· **Ingredients with biological limit values:**	
111-76-2 Glycol Ether EB (2-butoxyethanol)	
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

(Contd. on page 7)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 6)

67-56-1 Methanol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

· **Regulatory information** BEI: Guide to Occupational Exposure Values (BEI)
· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls**
Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.
· **Appropriate engineering controls** No further data; see section 7.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· **Protection of hands:**

Protective gloves

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**

Tightly sealed goggles

· **Limitation and supervision of exposure into the environment**
Keep away from drains, surface and ground waters.
Avoid release into the environment.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**
· **General Information**

· **Physical state**	Liquid
· **Color:**	Colored
· **Odor:**	Citrus
· **Odor threshold:**	Not determined
· **Melting point/Melting range:**	Undetermined
· **Boiling point/Boiling range:**	>100 °C (>212 °F)
· **Flammability:**	Not applicable

(Contd. on page 8)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 7)

· **Explosion limits:**	
· **Lower:**	Not determined
· **Upper:**	Not determined
· **Flash point:**	>93.3 °C (>199.9 °F)
· **Decomposition temperature:**	Not determined
· **pH-value at 20 °C (68 °F):**	13–14
· **Viscosity:**	
· **Kinematic:**	Not determined
· **Dynamic:**	Not determined
· **Solubility in / Miscibility with**	
· **Water:**	Fully miscible.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Vapor pressure at 20 °C (68 °F):**	23 hPa (17.3 mm Hg)
· **Density at 20 °C (68 °F):**	1 g/cm³ (8.345 lbs/gal)
· **Relative density**	Not determined
· **Bulk density:**	1,000 kg/m³
· **Vapor density**	Not determined
· **Particle characteristics**	Not applicable
· **Other information**	
· **Appearance:**	
· **Form:**	Liquid
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not self-igniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Solvent content:**	
· **Organic solvents:**	<5.5 %
· **VOC content:**	5.1–<5.11 % 51.1 g/l / 0.43 lb/gal
· **Change in condition**	
· **Oxidizing properties**	None
· **Evaporation rate**	Not determined

10 Stability and reactivity

· **Reactivity**
The product is stable under normal conditions.
No further relevant information available.
· **Chemical stability** Stable under normal conditions.
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:**
Strong oxidizing agents.
Strong bases
· **Hazardous decomposition products:** Oxides of carbon (COx)

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
ATE (Acute Toxicity Estimate)		
Oral	LD50	4,064 mg/kg
Dermal	LD50	10,536 mg/kg (rab)
Inhalative	LC50/4 h	>78.6 mg/l

(Contd. on page 9)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 8)

1310-58-3 Potassium hydroxide		
Oral	LD50	273 mg/kg (Rat)
68603-42-9 Cocamide DEA		
Oral	LD50	1,600 mg/kg (Rat)
Dermal	LD50	12,200 mg/kg (Rabbit)
111-76-2 Glycol Ether EB (2-butoxyethanol)		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (Rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)
67-56-1 Methanol		
Oral	LD50	5,628 mg/kg (Rat)
Dermal	LD50	15,800 mg/kg (Rabbit)
Inhalative	LC50/4 h	128.2 mg/l (Rat)
	LC50/96 hours	15,400 Mg/l (trout)
111-42-2 Diethanolamine		
Oral	LD50	1,600 mg/kg (Rat)
Dermal	LD50	12,200 mg/kg (Rabbit)

· **Primary irritant effect:**
· **on the skin:** Strong caustic effect on skin and mucous membranes.
· **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
· **Sensitization:** Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
· **Interactive effects** No interactive effects between components are known.

· **Carcinogenic categories**
· **IARC (International Agency for Research on Cancer)**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

68603-42-9	Cocamide DEA	2B
111-76-2	Glycol Ether EB (2-butoxyethanol)	3
111-42-2	Diethanolamine	2B
5989-27-5	D-Limonene	3
93-15-2	Eugenyl methyl ether	2A

· **NTP (National Toxicology Program)**
R - Reasonably anticipated to be a human carcinogen

93-15-2	Eugenyl methyl ether	R

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 *Reviewed on 04/24/2026*

Trade name: Easy

(Contd. of page 9)

· ***Alternative sources for toxicological information***
No non-standard sources for toxicological information were used.

12 Ecological information

· ***Toxicity***

· ***Aquatic toxicity:***	
111-76-2 Glycol Ether EB (2-butoxyethanol)	
EC50	1,815 mg/kg (Water flea)
67-56-1 Methanol	
EC50	10,000 mg/kg (daphnia) 22,000 mg/kg (Green algae)

· ***Persistence and degradability*** *No further relevant information available.*
· ***Bioaccumulative potential*** *No further relevant information available.*
· ***Mobility in soil*** *No further relevant information available.*
· ***Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable*
· ***vPvB:*** *Not applicable*
· ***Other adverse effects***
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

13 Disposal considerations

· ***Waste treatment methods***
· ***Recommendation:***
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Observe all federal, state and local environmental regulations when disposing of this material.

· ***Uncleaned packagings:***
· ***Recommendation:*** *Disposal must be made according to official regulations.*
· ***Recommended cleansing agent:*** *Water, if necessary with cleansing agents.*

14 Transport information

· ***UN-Number***
· ***DOT, IMDG, IATA*** *UN1719*
· ***UN proper shipping name***
· ***DOT*** *Caustic alkali liquids, n.o.s. (Potassium hydroxide)*
· ***IMDG*** *CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE)*
· ***IATA*** *Caustic alkali liquid, n.o.s. (POTASSIUM HYDROXIDE)*
· ***Transport hazard class(es)***

· ***DOT***

· ***Class*** *8 Corrosive substances*

(Contd. on page 11)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 10)

· **Label** 8

· **IMDG, IATA**

· **Class**	8 Corrosive substances
· **Label**	8
· **Packing group**	
· **DOT, IMDG, IATA**	II
· **Environmental hazards:**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Special precautions for user**	Warning: Corrosive substances
· **Hazard identification number (Kemler code):**	80
· **EMS Number:**	F-A,S-B
· **Segregation groups**	(SGG18) Alkalis
· **Stowage Category**	A
· **Segregation Code**	SG22 Stow "away from" ammonium salts SG35 Stow "separated from" SGG1-acids
· **UN "Model Regulation":**	UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE), 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**	
67-56-1	Methanol
111-42-2	Diethanolamine

· **Proposition 65**

· **Chemicals known to cause cancer:**

WARNING: This product can expose you to chemicals including [one or more listed chemical] which is [are] known to the State of California to cause cancer [or birth defects or other reproductive harm]. For more information, go to www.P65Warnings.ca.gov.

68603-42-9	Cocamide DEA
111-42-2	Diethanolamine
93-15-2	Eugenyl methyl ether

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	Methanol

· **New Jersey Right-to-Know List:**

1310-58-3	Potassium hydroxide
111-76-2	Glycol Ether EB (2-butoxyethanol)
67-56-1	Methanol
56-81-5	Glycerol
111-42-2	Diethanolamine
138-86-3	Limonene
80-56-8	alpha-Pinene
1310-73-2	Sodium hydroxide
586-62-9	Terpinolene
8006-64-2	Turpentine, oil
93-15-2	Eugenyl methyl ether

· **New Jersey Special Hazardous Substance List:**

1310-58-3	Potassium hydroxide	CO, R1
111-76-2	Glycol Ether EB (2-butoxyethanol)	CA, F2
67-56-1	Methanol	TE, F3
111-42-2	Diethanolamine	CO
80-56-8	alpha-Pinene	F3
1310-73-2	Sodium hydroxide	CO, R1
586-62-9	Terpinolene	F3
8006-64-2	Turpentine, oil	F3
93-15-2	Eugenyl methyl ether	CA

· **Pennsylvania Right-to-Know List:**

1310-58-3	Potassium hydroxide
111-76-2	Glycol Ether EB (2-butoxyethanol)
56-81-5	Glycerol
111-42-2	Diethanolamine
80-56-8	alpha-Pinene
1310-73-2	Sodium hydroxide
25265-71-8	Dipropylene glycol (isomer unspecified)

· **Pennsylvania Special Hazardous Substance List:**

1310-58-3	Potassium hydroxide	E
111-42-2	Diethanolamine	E
1310-73-2	Sodium hydroxide	E

· **EPA (Environmental Protection Agency)**

111-76-2	Glycol Ether EB (2-butoxyethanol)	NL

· **TLV (Threshold Limit Value)**

111-76-2	Glycol Ether EB (2-butoxyethanol)	A3
111-42-2	Diethanolamine	A3
80-56-8	alpha-Pinene	A4
127-91-3	beta-Pinene	A4

(Contd. on page 13)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 Reviewed on 04/24/2026

Trade name: Easy

(Contd. of page 12)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **PFAS**
None of the ingredients is listed.

· **Per- and polyfluoroalkyl substances (PFAS)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**

GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Disodium Cocoampho Dipropionate
Potassium hydroxide
Cocamide DEA
dipropylene glycol butyl ether
Limonene
· **Hazard statements**
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.
· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

(Contd. on page 14)

PERFORM MANUFACTURING

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 04/24/2026 *Reviewed on 04/24/2026*

Trade name: Easy

(Contd. of page 13)

· ***SDS created by:*** *Access GHS, LLC - 888-363-4870 - Team@access-ghs-sds.com*
· ***Date of previous version*** *01/27/2016*
· ***Version number of previous version:*** *1*
· ***Date of preparation*** *04/24/2026*
· ***Abbreviations and acronyms:***
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable liquids 2: Flammable liquids – Category 2
Flammable liquids 3: Flammable liquids – Category 3
Flammable liquids 4: Flammable liquids – Category 4
Acute toxicity - oral 3: Acute toxicity – Category 3
Acute toxicity - oral 4: Acute toxicity – Category 4
Skin corrosion 1A: Skin corrosion/irritation – Category 1A
Skin irritation 2: Skin corrosion/irritation – Category 2
Eye damage 1: Serious eye damage/eye irritation – Category 1
Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2
Specific target organ toxicity (single exposure) 1: Specific target organ toxicity (single exposure) – Category 1
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2