Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

1 Identification

· ***Product identifier***

· ***Product name:*** **Tiger**
· ***Other means of identification***

· ***Product number:*** 6650
· ***Relevant identified uses of the substance or mixture and uses advised against***
· ***Product Description:*** Super Double-Strength Degreaser

· ***Details of the supplier of the safety data sheet***
· ***Manufacturer/Supplier:***
Perform Mfg
1624 S. 45th St.
Kansas City, KS 66106
Customer Service: 913-722-1557
E-Mail: sales@performmfg.com
· ***Emergency telephone number:*** Infotrac: US & Canada: 1-800-535-5053 | International 1-352-323-3500

2 Hazard(s) identification

· ***Classification of the substance or mixture***

GHS05 Corrosion

Skin corrosion 1A	H314 Causes severe skin burns and eye damage.
Eye damage 1	H318 Causes serious eye damage.

GHS07

Sensitization - skin 1 H317 May cause an allergic skin reaction.

· ***Label elements***
· ***GHS label elements*** The product is classified and labeled according to the Globally Harmonized System (GHS).
· ***Hazard pictograms***

GHS05 GHS07

· ***Signal word*** Danger

· ***Hazard-determining components of labeling:***
COMPLEX ALKYL PHOSPHATE ESTER
Nonylphenol Polyethylene Ethoxylate
Disodium Metasilicate
Sodium Hydroxide
Disodium Cocoampho Dipropionate
· ***Hazard statements***
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
· ***Precautionary statements***
Do not breathe dusts or mists.
Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 1)

Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· ***Unknown acute toxicity:***
This value refers to knowledge of known, established toxicological or ecotoxicological values.
0 % of the mixture consists of component(s) of unknown toxicity.

· ***Information pertaining to particular dangers for man and environment:***

· ***Classification system:*** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· ***NFPA ratings (scale 0 - 4)***

Health = 3
Fire = 1
Reactivity = 0

· ***HMIS-ratings (scale 0 - 4)***

Health = *3
Fire = 1
Reactivity = 0

· ***Other hazards***

· ***Results of PBT and vPvB assessment***

· ***PBT:*** Not applicable

· ***vPvB:*** Not applicable

· ***Classification according to (d)(1)(ii) of § 1910.1200***
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· ***Hazards not otherwise classified (HNOC)***
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· ***Chemical characterization: Mixtures***

· ***Description:*** Mixture of the substances listed below with nonhazardous additions.

· ***Dangerous components:***		
CAS: 111-76-2 RTECS: KJ 8575000	Glycol Ether EB (2-butoxyethanol) Acute toxicity - oral 4, H302; Acute toxicity - dermal 4, H312; Acute toxicity - inhalation 4, H332; Skin irritation 2, H315; Eye irritation 2A, H319; Specific target organ toxicity (single exposure) 3, H335-H336; Flammable liquids 4, H227	≥5–<10%

(Contd. on page 3)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 2)

CAS: 68130-47-2	COMPLEX ALKYL PHOSPHATE ESTER Skin corrosion 1C, H314; Acute toxicity - dermal 4, H312	≥1–<5%
CAS: 127087-87-0	Nonylphenol Polyethylene Ethoxylate Eye damage 1, H318; Acute toxicity - oral 4, H302; Acute toxicity - inhalation 4, H332	≥1–<3%
CAS: 1310-73-2	Sodium Hydroxide Corrosive to metals 1, H290; Skin corrosion 1A, H314; Acute toxicity - oral 4, H302 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	≥1–<2%
CAS: 6834-92-0	Disodium Metasilicate Skin corrosion 1B, H314; Acute toxicity - oral 4, H302; Specific target organ toxicity (single exposure) 3, H335	≥1–<1.5%
CAS: 1310-58-3 RTECS: TT 2102000	Potassium hydroxide Skin corrosion 1A, H314; Acute toxicity - oral 4, H302 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	0.5–1.5%
CAS: 68604-71-7	Disodium Cocoampho Dipropionate Eye damage 1, H318; Sensitization - skin 1, H317	≥0.1–<1%

· ***Additional information:***
The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-aid measures

· ***Description of first aid measures***
· ***General information:*** Immediately remove any clothing soiled by the product.
· ***After inhalation:***
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
· ***After skin contact:***
Immediately wash with water and soap and rinse thoroughly.
Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.
Remove contaminated clothing and wash before reuse.
· ***After eye contact:***
Have eyes examined and tested by medical personnel.
If thermal burn occurs, flush area with cold water and get immediate medical attention.
Rinse opened eye for at least 15 minutes under running water.
Seek immediate medical attention.
If easy to do so, remove contact lenses if worn.
· ***After swallowing:*** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
· ***Most important symptoms and effects, both acute and delayed*** No further relevant information available.
· ***Indication of any immediate medical attention and special treatment needed*** Treat symptomatically.

5 Fire-fighting measures

· ***Extinguishing media***
· ***Suitable extinguishing agents:***
Use fire fighting measures that suit the environment.

(Contd. on page 4)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 3)

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· ***For safety reasons unsuitable extinguishing agents:*** No further relevant information.

· ***Special hazards arising from the substance or mixture***

During heating or in case of fire poisonous gases are produced.

· ***Advice for firefighters***

· ***Protective equipment:***

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· ***Personal precautions, protective equipment and emergency procedures***

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· ***For non-emergency personnel*** Use appropriate personal protection equipment (PPE).

· ***For emergency responders***

Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

· ***Environmental precautions:***

Dilute with plenty of water.

Do not allow to enter sewers / surface or ground water.

· ***Methods and material for containment and cleaning up:***

Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· ***Protective Action Criteria for Chemicals***

Protective Action Criteria (PACs) are essential components for planning and response to uncontrolled releases of hazardous chemicals.

· ***PAC-1:***

PAC 1: Mild, transient health effects.

111-76-2	Glycol Ether EB (2-butoxyethanol)	20 ppm
7320-34-5	Tetrapotassium pyrophosphate	0.73 mg/m3
127087-87-0	Nonylphenol Polyethylene Ethoxylate	12 mg/m3
1310-73-2	Sodium Hydroxide	0.50 mg/m3
6834-92-0	Disodium Metasilicate	3.5 mg/m3
1310-58-3	Potassium hydroxide	0.18 mg/m3
100-52-7	Benzaldehyde	17 ppm
67-56-1	methanol	530 ppm
84-66-2	Diethyl Phthalate	1.7 mg/m3

· ***PAC-2:***

PAC 2: Irreversible or other serious health effects that could impair the ability to take protective action.

111-76-2	Glycol Ether EB (2-butoxyethanol)	67 ppm
7320-34-5	Tetrapotassium pyrophosphate	8.1 mg/m3
127087-87-0	Nonylphenol Polyethylene Ethoxylate	130 mg/m3
1310-73-2	Sodium Hydroxide	5.0 mg/m3
6834-92-0	Disodium Metasilicate	38 mg/m3
1310-58-3	Potassium hydroxide	2.0 mg/m3

(Contd. on page 5)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 4)

100-52-7	Benzaldehyde	43 ppm
67-56-1	methanol	2100 ppm
84-66-2	Diethyl Phthalate	31 mg/m3

· ***PAC-3:***
PAC 3: Life-threatening health effects.

111-76-2	Glycol Ether EB (2-butoxyethanol)	700 ppm
7320-34-5	Tetrapotassium pyrophosphate	49 mg/m3
127087-87-0	Nonylphenol Polyethylene Ethoxylate	790 mg/m3
1310-73-2	Sodium Hydroxide	50 mg/m3
6834-92-0	Disodium Metasilicate	230 mg/m3
1310-58-3	Potassium hydroxide	54 mg/m3
100-52-7	Benzaldehyde	260 ppm
67-56-1	methanol	7200 ppm
84-66-2	Diethyl Phthalate	190 mg/m3

· ***Reference to other sections***
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· ***Precautions for safe handling***
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· ***Information about protection against explosions and fires:*** Keep respiratory protective device available.

· ***Conditions for safe storage, including any incompatibilities***
· ***Storage:***
· ***Requirements to be met by storerooms and receptacles:***
Store in a cool, dry place away from sparks and flame.
Keep out of reach of children.
Keep container closed when not in use.
Keep in properly labelled containers.
· ***Information about storage in one common storage facility:*** Not required
· ***Further information about storage conditions:*** Keep receptacle tightly sealed.
· ***Specific end use(s)*** No further relevant information available.

8 Exposure controls/personal protection

· ***Control parameters***
· ***Components with limit values that require monitoring at the workplace:***
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

111-76-2 Glycol Ether EB (2-butoxyethanol)	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin

(Contd. on page 6)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 5)

TLV	Long-term value: 97 mg/m³, 20 ppm BEI, A3
1310-73-2 Sodium Hydroxide	
PEL	Long-term value: 2 mg/m³
REL	Ceiling limit value: 2 mg/m³
TLV	Ceiling limit value: 2 mg/m³
1310-58-3 Potassium hydroxide	
REL	Ceiling limit value: 2 mg/m³
TLV	Ceiling limit value: 2 mg/m³

· ***Regulatory information***
PEL: Guide to Occupational Exposure Values (OSHA PELs)
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)

· ***Ingredients with biological limit values:***	
111-76-2 Glycol Ether EB (2-butoxyethanol)	
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· ***Regulatory information*** BEI: Guide to Occupational Exposure Values (BEI)
· ***Additional information:*** The lists that were valid during the creation of this SDS were used as basis.

· ***Exposure controls***
Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.
· ***Appropriate engineering controls*** No further data; see section 7.
· ***Personal protective equipment:***
· ***General protective and hygienic measures:***
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· ***Breathing equipment:***
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· ***Protection of hands:***

Protective gloves

· ***Material of gloves***
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· ***Penetration time of glove material***
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 6)

· ***Eye protection:***

Tightly sealed goggles

· ***Body protection:***

Protective work clothing

· ***Limitation and supervision of exposure into the environment***
Keep away from drains, surface and ground waters.
Avoid release into the environment.

9 Physical and chemical properties

· ***Information on basic physical and chemical properties***
· ***General Information***

· ***Physical state***	Liquid
· ***Color:***	Colored
· ***Odor:***	Characteristic
· ***Odor threshold:***	Not determined
· ***Melting point/Melting range:***	Undetermined
· ***Boiling point/Boiling range:***	100 °C (212 °F)
· ***Flammability:***	Not applicable
· ***Explosion limits:***	
· ***Lower:***	Not determined
· ***Upper:***	Not determined
· ***Flash point:***	>150 °C (>302 °F)
· ***Auto igniting:***	240 °C (464 °F)
· ***Decomposition temperature:***	Not determined
· ***pH-value at 20 °C (68 °F):***	13–14
· ***Viscosity:***	
· ***Kinematic:***	Not determined
· ***Dynamic:***	Not determined
· ***Solubility in / Miscibility with***	
· ***Water:***	Fully miscible.
· ***Partition coefficient (n-octanol/water):***	Not determined
· ***Vapor pressure at 20 °C (68 °F):***	23 hPa (17.3 mm Hg)
· ***Density at 20 °C (68 °F):***	1.01742–1.0215 g/cm³ (8.49037–8.52442 lbs/gal)
· ***Relative density***	Not determined
· ***Bulk density:***	>1,019–1,021 kg/m³
· ***Vapor density***	Not determined
· ***Particle characteristics***	Not applicable

· ***Other information***

· ***Appearance:***	
· ***Form:***	Liquid
· ***Important information on protection of health and environment, and on safety.***	
· ***Ignition temperature:***	Product is not self-igniting.
· ***Danger of explosion:***	Product does not present an explosion hazard.

(Contd. on page 8)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 7)

· ***Solvent content:***
· ***Organic solvents:*** <9.1 %
· ***VOC content:*** <9.13 %
>92.9–93.3 g/l / 0.78 lb/gal
· ***Change in condition***
· ***Oxidizing properties*** None
· ***Evaporation rate*** Not determined

10 Stability and reactivity

· ***Reactivity***
The product is stable under normal conditions.
No further relevant information available.
· ***Chemical stability*** Stable under normal conditions.
· ***Thermal decomposition / conditions to be avoided:*** No decomposition if used according to specifications.
· ***Possibility of hazardous reactions*** No dangerous reactions known.
· ***Conditions to avoid*** No further relevant information available.
· ***Incompatible materials:*** No further relevant information available.
· ***Hazardous decomposition products:*** No dangerous decomposition products known.

11 Toxicological information

· ***Information on toxicological effects***
· ***Acute toxicity:***

· ***LD/LC50 values that are relevant for classification:***		
ATE (Acute Toxicity Estimate)		
Oral	LD50	7,537 mg/kg
Dermal	LD50	>3,808 mg/kg
Inhalative	LC50/4 h	26.8–29.2 mg/l

111-76-2 Glycol Ether EB (2-butoxyethanol)		
Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (Rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)
68130-47-2 COMPLEX ALKYL PHOSPHATE ESTER		
Oral	LD50	>2,500 mg/kg (Rat)
Dermal	LD50	>1,000 mg/kg (Rat)
Inhalative	LC50/96 hours	5.5 Mg/l (trout)
127087-87-0 Nonylphenol Polyethylene Ethoxylate		
Oral	LD50	16,000 mg/kg (Rat)
Dermal	LD50	4,490 mg/kg (Rabbit) 24 hr occluded contact
Inhalative	LC50/96 hours	3.8–6.2 Mg/l (pim)
1310-73-2 Sodium Hydroxide		
Oral	LD50	2,000 mg/kg (Rat)
6834-92-0 Disodium Metasilicate		
Oral	LD50	1,280 mg/kg (Rat)

(Contd. on page 9)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 8)

1310-58-3 Potassium hydroxide		
Oral	LD50	273 mg/kg (Rat)

· ***Primary irritant effect:***
· ***on the skin:*** Strong caustic effect on skin and mucous membranes.
· ***on the eye:***
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
· ***Sensitization:*** Sensitization possible through skin contact.
· ***Additional toxicological information:***
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
· ***Interactive effects*** No interactive effects between components are known.

· ***Carcinogenic categories***
· ***IARC (International Agency for Research on Cancer)***
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

111-76-2	Glycol Ether EB (2-butoxyethanol)	3

· ***NTP (National Toxicology Program)***
None of the ingredients is listed.

· ***OSHA-Ca (Occupational Safety & Health Administration)***
None of the ingredients is listed.

· ***Alternative sources for toxicological information*** No non-standard sources for toxicological information were used.

12 Ecological information

· ***Toxicity***

· ***Aquatic toxicity:***	
111-76-2 Glycol Ether EB (2-butoxyethanol)	
EC50	1,815 mg/kg (Water flea)
127087-87-0 Nonylphenol Polyethylene Ethoxylate	
EC50	1,000 mg/kg (daphnia)
1310-73-2 Sodium Hydroxide	
EC50	40 mg/kg (daphnia)

· ***Persistence and degradability*** No further relevant information available.
· ***Bioaccumulative potential*** No further relevant information available.
· ***Mobility in soil*** No further relevant information available.
· ***Results of PBT and vPvB assessment***
· ***PBT:*** Not applicable
· ***vPvB:*** Not applicable
· ***Other adverse effects***
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 3 (Self-assessment): extremely hazardous for water

(Contd. on page 10)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 9)

Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even extremely small quantities leak into the ground.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

13 Disposal considerations

· ***Waste treatment methods***
· ***Recommendation:***
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Observe all federal, state and local environmental regulations when disposing of this material.
· ***Waste disposal key:***
US EPA RCRA waste code D002 (corrosive hazardous wastes). The regulations at 40 CFR section 261.22.

· ***Uncleaned packagings:***
· ***Recommendation:*** Disposal must be made according to official regulations.
· ***Recommended cleansing agent:*** Water, if necessary with cleansing agents.

14 Transport information

· ***UN-Number***
· ***DOT, IMDG, IATA*** UN3265
· ***UN proper shipping name***
· ***DOT*** Corrosive liquid, acidic, organic, n.o.s. (COMPLEX ALKYL PHOSPHATE ESTER, Sodium hydroxide)
· ***IMDG*** CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (COMPLEX ALKYL PHOSPHATE ESTER, SODIUM HYDROXIDE)
· ***IATA*** Corrosive liquid, acidic, organic, n.o.s. (COMPLEX ALKYL PHOSPHATE ESTER, SODIUM HYDROXIDE)
· ***Transport hazard class(es)***

· ***DOT***

· ***Class*** 8 Corrosive substances
· ***Label*** 8

· ***IMDG, IATA***

· ***Class*** 8 Corrosive substances
· ***Label*** 8
· ***Packing group***
· ***DOT, IMDG, IATA*** II
· ***Environmental hazards:*** Product contains environmentally hazardous substances: Nonylphenol Polyethylene Ethoxylate
· ***Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code*** Not applicable

(Contd. on page 11)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 10)

· ***Transport/Additional information:***

· ***DOT***

· ***Quantity limitations***	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L

· ***IMDG***

· ***Limited quantities (LQ)***	1L
· ***Excepted quantities (EQ)***	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· ***Special precautions for user***	Warning: Corrosive substances
· ***Hazard identification number (Kemler code):***	80
· ***EMS Number:***	F-A,S-B
· ***Segregation groups***	(SGG1) Acids
· ***Stowage Category***	B
· ***Stowage Code***	SW2 Clear of living quarters.
· ***Segregation Code***	SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides
· ***UN "Model Regulation":***	UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (COMPLEX ALKYL PHOSPHATE ESTER, SODIUM HYDROXIDE), 8, II

15 Regulatory information

· ***Safety, health and environmental regulations/legislation specific for the substance or mixture***

· ***TSCA (Toxic Substances Control Act):***		
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
111-76-2	Glycol Ether EB (2-butoxyethanol)	ACTIVE
7320-34-5	Tetrapotassium pyrophosphate	ACTIVE
68130-47-2	COMPLEX ALKYL PHOSPHATE ESTER	ACTIVE
127087-87-0	Nonylphenol Polyethylene Ethoxylate	ACTIVE
1310-73-2	Sodium Hydroxide	ACTIVE
6834-92-0	Disodium Metasilicate	ACTIVE
1310-58-3	Potassium hydroxide	ACTIVE
68081-81-2	Benzenesulfonic acid, mono-C10-16-alkyl derivatives, sodium salts	ACTIVE
100-52-7	Benzaldehyde	ACTIVE
68604-71-7	Disodium Cocoampho Dipropionate	ACTIVE
67-56-1	methanol	ACTIVE
84-66-2	Diethyl Phthalate	ACTIVE

· ***Hazardous Air Pollutants***	
67-56-1	methanol

· ***Proposition 65***

· ***Chemicals known to cause cancer:***
None of the ingredients is listed.

· ***Chemicals known to cause reproductive toxicity for females:***
None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 11)

· ***Chemicals known to cause reproductive toxicity for males:***

None of the ingredients is listed.

· ***Chemicals known to cause developmental toxicity:***

67-56-1	methanol

· ***New Jersey Right-to-Know List:***

111-76-2	Glycol Ether EB (2-butoxyethanol)
1310-73-2	Sodium Hydroxide
1310-58-3	Potassium hydroxide
100-52-7	Benzaldehyde
67-56-1	methanol
84-66-2	Diethyl Phthalate

· ***New Jersey Special Hazardous Substance List:***

111-76-2	Glycol Ether EB (2-butoxyethanol)	CA, F2
1310-73-2	Sodium Hydroxide	CO, R1
1310-58-3	Potassium hydroxide	CO, R1
67-56-1	methanol	TE, F3

· ***Pennsylvania Right-to-Know List:***

111-76-2	Glycol Ether EB (2-butoxyethanol)
1310-73-2	Sodium Hydroxide
1310-58-3	Potassium hydroxide
100-52-7	Benzaldehyde
84-66-2	Diethyl Phthalate

· ***Pennsylvania Special Hazardous Substance List:***

1310-73-2	Sodium Hydroxide	E
1310-58-3	Potassium hydroxide	E
84-66-2	Diethyl Phthalate	E

· ***EPA (Environmental Protection Agency)***

111-76-2	Glycol Ether EB (2-butoxyethanol)	NL
84-66-2	Diethyl Phthalate	D

· ***TLV (Threshold Limit Value)***

111-76-2	Glycol Ether EB (2-butoxyethanol)	A3
84-66-2	Diethyl Phthalate	A4

· ***NIOSH-Ca (National Institute for Occupational Safety and Health)***

None of the ingredients is listed.

· ***PFAS***

None of the ingredients is listed.

· ***Per- and polyfluoroalkyl substances (PFAS)***

None of the ingredients is listed.

· ***GHS label elements*** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 13)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 12)

· ***Hazard pictograms***

GHS05 GHS07

· ***Signal word*** Danger

· ***Hazard-determining components of labeling:***
COMPLEX ALKYL PHOSPHATE ESTER
Nonylphenol Polyethylene Ethoxylate
Disodium Metasilicate
Sodium Hydroxide
Disodium Cocoampho Dipropionate

· ***Hazard statements***
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

· ***Precautionary statements***
Do not breathe dusts or mists.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· ***Chemical safety assessment:*** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· ***SDS created by:*** Access GHS, LLC - 888-363-4870 - Team@access-ghs-sds.com
· ***Date of previous version*** 07/20/2023
· ***Version number of previous version:*** 2
· ***Date of preparation*** 06/17/2026
· ***Abbreviations and acronyms:***
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

(Contd. on page 14)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 06/17/2026 *Reviewed on 06/17/2026*

Product name: **Tiger**

(Contd. of page 13)

HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable liquids 4: Flammable liquids – Category 4
Corrosive to metals 1: Corrosive to metals – Category 1
Acute toxicity - oral 4: Acute toxicity – Category 4
Skin corrosion 1A: Skin corrosion/irritation – Category 1A
Skin corrosion 1B: Skin corrosion/irritation – Category 1B
Skin corrosion 1C: Skin corrosion/irritation – Category 1C
Skin irritation 2: Skin corrosion/irritation – Category 2
Eye damage 1: Serious eye damage/eye irritation – Category 1
Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - skin 1: Skin sensitisation – Category 1
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3